

Technical Specs

Hammerhead XT

PARAMETER	HAMMERHEAD XT
Model Number	AR302
Depth Rating	1,000m (3,300ft) air-filled; 6,000m (19,700ft) oil-filled
Input Voltage	10–40VDC
Rated Torque (per axis @24V)	13.6N-m (10ft-lb)
Current Draw (per axis @24V)	No load: 120 mA, Rated load: 750mA; Limit: 850mA
Rotation Range (per axis)	Unlimited; soft limits may be set by user commands
Speed Range	Continuously variable 0–100%, in 1% increments
No Load Speed (max)	5 RPM
Payload	10kg (22Lbs)
Position Feedback (each axis)	Absolute. Resolution: 0.1°; Accuracy: 0.2°
Gearbox Backlash	<i>*Backlash is measured and reported by encoders - 1.0° (60 arc-min)</i>
Control	Multidrop RS232 or RS485 (2-wire); 254 soft-addresses
Housing Material	316 stainless steel or 6061-T6 AHC black anodized aluminum
Weight in Air (air-filled)	316 SS: 2.8kg (6.2Lbs); 6061AL: 1.6kg (3.5Lbs)
Weight in Air (oil-filled)	316 SS: 3.2kg (7.1Lbs); 6061AL: 2.0kg (4.4Lbs)
Weight in Water (air-filled)	316 SS: 2.0kg (4.4Lbs); 6061AL: 800g (1.8Lbs)
Weight in Water (oil-filled)	316 SS: 2.4kg (5.3Lbs); 6061AL: 1.2kg (2.6Lbs)
Operating Temperature	-10°C to 40°C
Connector Pinout (Subconn MCBH4M or MCPBOF4M standard)	1: GND 3: RS232 RX (in) or RS485 (A) 2: +10–40Vdc 4: RS232 TX (out) or RS485(B) <i>*Additional pins on custom connectors will be left unused</i>

